

PRO-LL 5w30

HIGH PERFORMANCE FULL SYNTHETIC ENGINE OIL

DESCRIPTION

Synthetic high performance engine oil produced with special selected base oils with a high viscosity index and a well balanced choice of advanced additives. Provides optimum protection and extended engine life and reliability. Combines exceptional anti-wear performance and outstanding high temperature protection with excellent cold start characteristics. This motor oil also contributes to the extension of the lifetime of particle filters.

PROPERTIES

- Fuel economy.
- High and very stable viscosity index.
- Superior resistance against shearing.
- Fast cold start.
- Safe lubrication film at extreme temperatures.
- Flexible and extended oil drain intervals.
- High protection against wear.
- Low SAPS / DPF- compatible.

APPLICATION

Suitable for both turbocharged and normally aspirated engines to ensure maximum economy and reduced emissions (CO₂). LOW SAPS technology. Specially designed to optimum performance in today's VW-Group engines where VW 507.00/504.00 specifications are required. Apply the correct amount of oil indicated in the operating instructions of the vehicle and engine manufacture.

TYPICALS

Density at 15 °C	0,851 kg/l
Viscosity -30 °C	5950 mPa.s
Viscosity 40 °C	69,20 mm²/s
Viscosity 100 °C	12,00 mm²/s
Viscosity Index	171
Flash Point COC	230 °C
Pour Point	-42 °C
Total Base Number	6,7 mgKOH/g
Sulphate Ash	0,67 %

SPECIFICATIONS

ACEA C2/C3	FIAT 9.55535-S1
VW 504.00/507.00	GM DEXOS 2
MB-Approval 229.51	
BMW LL-04	
Porsche C30	

PACKAGING

1L can (12 x 1L box)
5L can (4 x 5L box)
60 L drum
208 L drum

